



PIN OUT

CN1	CN2	CN1	CN2
1	WHITE	14	WHITE
3	BROWN	19	ORANGE
5	DRAIN	17	DRAIN
4	WHITE	13	GREEN
6	BLUE	15	WHITE
2	DRAIN	16	GRAY
7	WHITE	18	RED
9	GREEN	8	BRAID+DRAIN
11	DRAIN		SHELL
10	WHITE		SHELL
12	RED		
	DRAIN		

NOTE:

- Electrical test:
 - 100% open short & miss wire test;
 - Insulation resistance:DC 300V 10M ohm;
 - Contact resistance:5 ohm;
 - Computer+Monitor TEST 3840*2160@60Hz
- Features
 - Data Transfer: 18Gbps
 - 3840×2160@60Hz 4096×2160@60hz resolution 4:4:4
 - Integrated HDMI Ethernet Channel(HEC) for Network data transfer up to 100Mbit/s
 - Supports 3D/HDCP2.2/EDID/HDR/ARC/CEC/8PCM/Dolby Digital/DTS/MPEG/DVD-Audio/SACD/Dolby Digital Plus/True HD/dts-HD
- PRINT WORD:High Speed HDMI® Cable with Ethernet RECYCLED
- Operating Temperature:-10℃~+60℃
- Storage Temperature:-20℃~ +80℃
- RoHS and Reach Compliant
- The proportion for the recycled material is more than 50%.

MATERIAL LIST:

④	Outer mold	Black RECYCLED PVC	2	
③	Inner mold	LDPE	2	
②	HDMI A/M	19P A/M,Black insulation The Pin Gold Plating, the shell for Gold Plating	2	
①	Cable	(30AWG BC*1P+E+AM)*5C+30AWG BC*4C+ADB RECYCLED PVC JACKET OD6.3±0.2MM	L±T	
NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK
		NEW	2023-12-19	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

11.45.5733	Ultra HDMI + Ethernet Cable, M/M, 4K60, 3m	3000±50
11.45.5732	Ultra HDMI + Ethernet Cable, M/M, 4K60, 2m	2000±30
11.45.5731	Ultra HDMI + Ethernet Cable, M/M, 4K60, 1m	1000±20
ITEM NO.	DESC.	LENGTH (mm)

