

Datenblatt Art. 350.091

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

PRIMO 2 Steckdosenleiste / PRIMO 2 power strip

Elektrische Kenngrößen Electrical parameters

Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50Hz	Frequency	50Hz

Netzanschluss Power supply

Zuleitung	2,0m H05VV-F 3G1,5mm ²	Supply cable	2,0m H05VV-F 3G1,5mm ²
Farbe Zuleitung Wiederanschließbar	Schwarz	Colour supply cable Rewirable	Black
Stecker	CEI 23-50 S17 (Type L)	Plug	CEI 23-50 S17 (Type L)

Stromausgang Power output

Steckdosen	Socket outlets
3x CEI 23-50 P40	3x CEI 23-50 P40
2-polig mit Schutzkontakt	2-pole with earthing contact
Mit erhöhtem Berührungsschutz	With shutter
Schwarz, ähnlich RAL 9005, 35°	Black, similar to RAL 9005, 35°
16A / 250V~, IP20	16A / 250V~, IP20

Funktionsmodule Function modules

Schalter	Switch
Grün beleuchtet	Green illuminated

Weitere Produkteigenschaften Further product attributes

Plattform	Standard (kHE)	Plattform	Standard (kHE)
Material		Material	
Gehäuse: Aluminium, eloxiert schwarz, ähnlich RAL 9005		Housing: Aluminium, anodised black, similar to RAL 9005	
Schwarze Design-Endkappen		Black design endcaps	
Abdeckung: PA6 GF30 850°C, schwarz ähnlich RAL 9005		Cover: PA6 GF30 850°C, black similar to RAL 9005	

Lieferumfang

1x PRIMO 2 Steckdosenleiste

Im Karton

Scope of delivery

1x PRIMO 2 power strip

In carton

Umgebungsbedingungen

Maximale Höhe	0 - 3000m
Umgebungstemperatur bei Montage und Nutzung Vor direkter Sonneneinstrahlung schützen.	5°C – 35°C
Umgebungstemperatur bei Transport und Lagerung	-25°C - 60°C
Relative Luftfeuchtigkeit (nicht kondensierend)	5 – 95%
Schutzart	IP20

Environmental conditions

Maximum height	0 - 3000m
Surrounding temperature during mounting and use Protect from direct sunlight.	5°C – 35°C
Surrounding temperature during transport and storage	-25°C - 60°C
Relative humidity (non-condensing)	5 – 95%
Protection type	IP20

Konformität

Angewandte Normen	CEI 23-50
--------------------------	-----------

Conformity

Applied standards	CEI 23-50
--------------------------	-----------

