

## Datenblatt Art. 927.257

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

### KAPSA XS

Elektrische Kenngrößen		Electrical parameters	
<b>Nennstrom / Bemessungsspannung</b>	13A / 250V~	<b>Rated current / rated voltage</b>	13A / 250V~
<b>Frequenz</b>	50 Hz	<b>Frequency</b>	50 Hz
Netzanschluss		Power supply	
<b>Zuleitung</b>	<b>0,2m   H05VV-F   3G1,5mm<sup>2</sup></b>	<b>Supply cable</b>	<b>0,2m   H05VV-F   3G1,5mm<sup>2</sup></b>
Farbe Zuleitung	Schwarz	Colour supply cable	Black
<b>Stecker</b>	<b>Wieland GST18i3</b>	<b>Plug</b>	<b>Wieland GST18i3</b>
Stromausgang		Power output	
<b>Steckdosen</b>	<b>1x UK BS 1363 (Type G)</b>	<b>Socket outlets</b>	<b>1x UK BS 1363 (Type G)</b>
2-polig mit Schutzkontakt	Mit erhöhtem Berührungsschutz	2-pole with earthing contact	With shutter
Schwarz, ähnlich RAL 9005, 90°	Integrierte Sicherung 3,15 A	Black, similar to RAL 9005, 90°	Integrated Fuse 3,15A
13A / 250V~, IP20		13A / 250V~, IP20	
Funktionsmodule		Function modules	
<b>USB-Charger</b>		<b>USB charger</b>	
Doppelcharger	3,1A 5V DC	Double charger	3,1A 5V DC
Weitere Produkteigenschaften		Further product attributes	
<b>Plattform</b>	Standard (kHE)	<b>Plattform</b>	Standard (kHE)
<b>Material</b>		<b>Material</b>	
Gehäuse: Aluminium, eloxiert		Housing Aluminium, anodised	
Abdeckung: PA6 850°C, schwarz ähnlich RAL 9005		Cover: PA6 GF30 850°C, black similar to RAL 9005	
<b>Lieferumfang</b>		<b>Scope of delivery</b>	
1x Steckdosenleiste KAPSA XS		1x Power strip KAPSA XS	
Im Karton		In carton	
<b>Optionales Zubehör</b>		<b>Optional accessories</b>	
Deckel KAPSA XS		KAPSA Lid XS	

Umgebungsbedingungen		Environmental conditions	
<b>Umgebungstemperatur bei Montage und Nutzung</b> Vor direkter Sonneneinstrahlung schützen.	5°C – 40°C	<b>Surrounding temperature during mounting and use</b> Protect from direct sunlight.	5°C – 40°C
<b>Umgebungstemperatur bei Transport und Lagerung</b>	-25°C - 60°C	<b>Surrounding temperature during transport and storage</b>	-25°C - 60°C
<b>Relative Luftfeuchtigkeit (nicht kondensierend)</b>	5 – 95%	<b>Relative humidity (non-condensing)</b>	5 – 95%
<b>Schutzart</b>	IP20	<b>Protection type</b>	IP20
Konformität / Approbation		Conformity / Approval	
<b>Bauart geprüft</b>	BS 1363	<b>Type approved</b>	BS 1363

Zeichnung  
BAN0020333

Drawing

