

## Datenblatt Art. 902.319

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

### DESK 2

Elektrische Kenngrößen		Electrical parameters	
<b>Nennstrom / Bemessungsspannung</b>	16A / 250V~	<b>Rated current / rated voltage</b>	16A / 250V~
<b>Frequenz</b>	50 / 60Hz	<b>Frequency</b>	50 / 60Hz
Netzanschluss		Power supply	
<b>Zuleitung</b>	0,2m H05VV-F 3G1,5mm <sup>2</sup>	<b>Supply cable</b>	0,2m H05VV-F 3G1,5mm <sup>2</sup>
<b>Stecker</b>	Wieland GST18i3	<b>Plug</b>	Wieland GST18i3
Stromausgang		Power output	
<b>Steckdosen</b>		<b>Socket outlets</b>	
<b>2x CEE 7/3 (Type F)</b>		<b>2x CEE 7/3 (Type F)</b>	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Mit erhöhtem Berührungsschutz		With shutter	
Schwarz, ähnlich RAL 9005, 35°		Black, similar to RAL 9005, 35°	
16A 250V~, IP20		16A 250V~, IP20	
Weitere Produkteigenschaften		Further product attributes	
<b>Material</b>		<b>Material</b>	
Gehäuse: Aluminium, lackier in weiß ähnlich RAL 9010		Housing: Aluminium, lacquered in white similar to RAL9010	
Abdeckung: Kunststoff: PA6 GF 30 V1 , Glühdraht-Prüfung bis 850°C		Cover: Plastic: PA6 GF 30 V1, glow wire resistant up to 850°C	
<b>USB-Charger</b>		<b>USB charger</b>	
Doppelcharger	3,1A / 5VDC	Double charger	3,1A / 5VDC
<b>Lieferumfang</b>		<b>Scope of delivery</b>	
1x DESK Steckdosenleiste		1x DESK power strip	
2xHaltewinkel		2x mounting brackets	
Im Karton		In carton	

