



L±T mm: 3000±15mm (19.99.1176)
 L±T mm: 5000±25mm (19.99.1177)
 L±T mm: 10000±50mm (19.99.1178)

L±T mm

Notes;

- 1.Plug: 16A 250V~ Clear injection, no scrath and dirt
- 2.Cable:H05VV-F 3G1.5 mm²Jacket $\phi 8.5 \pm 0.2$ Conductor 48×0.20 , Core $\phi 2.4 \pm 0.1$
 Cable Mark: <VDE> H05VV-F 3G1.5mm² Ningbo Yuxin Appliance Co.,Ltd
- 3.Test: Hi-Pot : Inner Voltage AC2500V/1S、 External Voltage AC6000V/1S、 current leakage 1mA, insulation resistance no less than 50M Ω , no strike out

SECOMP

P.N	NEDIS	19.99.1176/19.99.1177/19.99.1178	Drw.N	JT-TP-0104	
Dre By	Ni Shaojian	VALUE Power Extension Cable	Date		
Check By		$.x \pm 0.15$ $.x' \pm 0.15$ $.xx \pm 0.25$ $.xx' \pm 0.25$ $.xxx \pm 0.38$ $.xxx' \pm 0.38$	比例	1 : 1	
			投影		Unit
			Color	White	

1
2
3
4
5

1
2
3
4
5

A

B

C

D

E

A

D

E