


PIN OUT

	CN1 (568B)		CN2 (568B)
WHITE-ORANGE	1	↔	1 WHITE-ORANGE
ORANGE	2	↔	2 ORANGE
WHITE-GREEN	3	↔	3 WHITE-GREEN
GREEN	6	↔	6 GREEN
BLUE	4	↔	4 BLUE
WHITE-BLUE	5	↔	5 WHITE-BLUE
WHITE-BROWN	7	↔	7 WHITE-BROWN
BROWN	8	↔	8 BROWN



NOTE:

1. ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
2. FLUKE Channel TEST:
TEST LIMIT:ISO11801 Channel Class Ea
3. Working temperature:-10°C~+60°C
Storage temperature:-20°C~+75°C
4. RoHS2.0 AND REACH compliant
5. Spray WORD:CAT6A U/UTP 4x2x32AWG/7 Ultraflex LSZH-TPE ISO11801 & EN50173 & ANSI/TIA568C. 2
6. Minimum of the bending radius is 15mm(Suitable for all meters)

MATERIAL LIST

NO.	PARTS NAME	SPECIFICATION STANDARD	QTY	REMARK
③	OVER MOLD	75A PVC RED(PANTONE199C)	2	
②	CONNECTOR	RJ45 8P8C UNSHIELDED PLUG, PIN GOLD PLATED 3U", COLOUR:TRANSPARENT	2	
①	CABLE	CAT.6A U/UTP CABLE (32AWG BC*1P)*4P JACKET:ULTRAFLEX LSZH-TPE RED(PANTONE199C) OD:3.4±0.2MM	1	

Item NO.	Length (mm)
21.44.3910	150±10
21.44.3911	300±10
21.44.3912	500±20
21.44.3913	1000±20
21.44.3914	1500±30
21.44.3915	2000±30
21.44.3916	3000±50
21.44.3917	5000±100

DESC.	ROLINE GREEN Cat.6A U/UTP Patch cord 10G Slim Type Ultraflex LSZH-TPE, red
-------	--

SECOMP

		NEW	2022-07-01	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.