


WIRING DIAGRAM



NOTE:

1. ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
2. FLUKE Channel LINK TEST:
TEST LIMIT:ISO11801 Channel Class EA
3. Working temperature:-20°C~+75°C
Storage temperature:-20°C~+80°C
4. RoHS AND REACH compliant
5. Spray WORD:CAT6A S/FTP with 600MHz cat.7 raw cable
4x2x26AWG/7 RECYCLED TPE ISO11801 & EN50173 & ANSI/TIA568.2-D
6. Minimum of the bending radius is 4*OD (Suitable for all meters)

MATERIAL LIST:

③	OVER MOLD	RECYCLED PVC WHITE RAL9003	2	
②	PLUG	RJ45 8P8C SHIELDED PLUG PIN GOLD PLATED 3U", THE SHELL PLATED NICKEL, COLOUR: TRANSPARENT GREEN	2	
①	CABLE	S/FTP CAT. 7 26AWG (BC+RECYCLED INSULATION+AL-FOIL)*4P+ BRAID (AL-MG) JACKET: RECYCLED TPE WHITE RAL9003 OD: 6.0±0.2MM	1	
NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK
		NEW	2023-11-30	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

21.45.3269	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 20m	20000±300	53.40%
21.45.3268	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 15m	15000±300	53.40%
21.45.3267	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 10m	10000±300	53.40%
21.45.3266	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 7m	7000±150	53.30%
21.45.3265	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 5m	5000±100	53.30%
21.45.3263	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 3m	3000±50	53.10%
21.45.3262	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 2m	2000±30	53.00%
21.45.3264	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 1.5m	1500±30	52.90%
21.45.3261	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 1m	1000±20	52.60%
21.45.3260	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 0.5m	500±20	52.10%
21.45.3276	ROLINE RECYCLED S/FTP PatchCord Cat6A/C1.EA, TPE, white, 0.3m	300±10	51.70%
ITEM NO.	DESC.	LENGTH (mm)	The proportion of RECYCLED certification materials

