

Brother TD-2130N

Marke : Brother

Artikel-Code: TD-2130NXX1

Produktname : TD-2130N

- Thermodirekt - Druckverfahren
- 152,4 mm / Sekunde max. Druckgeschwindigkeit
- ZPLII- und ESC/P-Emulation
- 56 mm max. Druckbreite
- 300 dpi Auflösung
- USB- und serielle Schnittstelle

203x203 dpi, 152.4 mm/sec, USB, RS-232C, LAN

Brother TD-2130N. Drucktechnologie: Direkt Wärme, Maximale Auflösung: 300 x 300 DPI, Druckgeschwindigkeit (metrisch): 152,4 mm/sek. Produktfarbe: Weiß



| Drucken | | Design | |
|--------------------------------------|--|--------------------------------------|---|
| Drucktechnologie * | Direkt Wärme | Produktfarbe * | Weiß |
| Maximale Auflösung * | 300 x 300 DPI | Systemanforderung | |
| Druckgeschwindigkeit (metrisch) * | 152,4 mm/sek | Unterstützt Windows-Betriebssysteme | ✓ |
| Maximum Druckweite * | 5,6 cm | Betriebsbedingungen | |
| Maximum Druckerhöhe | 9,86 cm | Relative Luftfeuchtigkeit in Betrieb | 20 - 80% |
| Vertikaler Druck | ✓ | Luftfeuchtigkeit bei Lagerung | 20 - 80% |
| Papierhandhabung | | Betriebstemperatur | 5 - 40 °C |
| Autoabschneider | ✓ | Temperaturbereich bei Lagerung | -20 - 60 °C |
| Maximale Etikettenlänge | 1 m | Gewicht und Abmessungen | |
| Anschlüsse und Schnittstellen | | Breite | 110 mm |
| Ethernet/LAN * | ✓ | Tiefe | 215 mm |
| USB Anschluss * | ✓ | Höhe | 172 mm |
| Anzahl USB 2.0 Anschlüsse | 1 | Gewicht | 1,34 kg |
| RS-232 port | 1 | Lieferumfang | |
| Optionale Konnektivität | Ethernet, Seriell (RS-232), USB 2.0 | Mitgelieferte Kabel | USB |
| Leistungen | | Treiber enthalten | ✓ |
| Flash-Speicher | 6 MB | Logistikdaten | |
| integrierte Barcodes | CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, Code-128 Codabar Library, Datenmatrix, EAN128, EAN13, EAN8, GS1-128, ITF, MaxiCode, Micro QR Code, MicroPDF417, PDF417, POSTNET, QR Code, UPC-A, UPC-E | Warentarifnummer (HS) | 84433210 |
| Anzahl Zeichensatz | 10 | Sonstige Funktionen | |
| Bandabschnitt | Automatisch | Zeichentabelle | Abicomp, ASCII, BRASCII, ISO 8859-15, ISO Latin 1, Italic, PC437, PC850, PC858, PC860, PC861, PC863, PC865, Roman 8 |
| Unterstreichung | ✓ | | |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 21-FEB-2024. Prints or copies of Information are only valid on the printed Publication date