

NETGEAR GS724TPv3 Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grau

Marke : NETGEAR

Artikel-Code: GS724TPP-300EUS

Produktname : GS724TPv3



NETGEAR GS724TPv3. Switch-Typ: Managed, Switch-Ebene: L2. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 24, Anzahl installierten SFP Module: 2. Routing-/Switching-Kapazität: 52 Gbit/s. Netzstandard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x. Power over Ethernet (PoE). Rack-Einbau



Management-Funktionen		Leistungen	
Switch-Typ *	Managed	Eingebauter Prozessor	✓
Switch-Ebene	L2	Prozessorhersteller	ARM
Web-basiertes Management	✓	Prozessor	ARM Cortex-A55
Cloud-verwaltet	✓	Prozessortaktfrequenz	800 MHz
Anschlüsse und Schnittstellen		Speicherkapazität	512 MB
Anzahl der basisschaltenden RJ-45 Ethernet Ports *	24	Flash-Speicher	64 MB
Basic Switching RJ-45 Ethernet Ports-Typ *	Gigabit Ethernet (10/100/1000)	Geräuschpegel	26,1 dB
Anzahl installierten SFP Module *	2	Mittlere Betriebsdauer zwischen Ausfällen (MTBF)	1784610 h
Optischer Kabelverbinder	SFP	Energie	
Netzwerk		Netzteil enthalten *	✓
Netzstandard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x	Stromverbrauch (Standardbetrieb)	11,3 W
VLAN-Unterstützung	✓	Stromverbrauch (max.)	20,69 W
Anzahl der VLANs	256	Power over Ethernet (PoE)	
Datenübertragung		Power over Ethernet (PoE) *	✓
Routing-/Switching-Kapazität *	52 Gbit/s	Anzahl Power over Ethernet plus (PoE+) Anschlüsse	24
Datenpaket-Pufferspeicher	1,5 MB	Power over Ethernet (PoE) Leistung pro Anschluss	190 W
Sicherheit		Gesamtleistung Power over Ethernet (PoE)	231,07 W
DHCP-Funktionen	DHCP client, DHCP snooping	Betriebsbedingungen	
Zugriffskontrollliste	✓	Betriebstemperatur	0 - 50 °C
Zugriffskontrollliste (ACL) IPv4-Einträge	100	Temperaturbereich bei Lagerung	-20 - 70 °C
IGMP-Snooping	✓	Relative Luftfeuchtigkeit in Betrieb	0 - 95%
Multicast-Funktionen		Luftfeuchtigkeit bei Lagerung	0 - 95%
Multicast Unterstützung	✓	Gewicht und Abmessungen	
Anzahl der gefilterten Multicast-Gruppen	512	Breite	440 mm
Design		Tiefe	257 mm
Rack-Einbau *	✓	Höhe	43,2 mm
Produktfarbe	Grau	Gewicht	3,15 kg
LED-Anzeigen	Aktivität, Link, PoE, Leistung, Geschwindigkeit, Ja		
Ungenutzter Lüfter-Support	✓		

Design

Anzahl Lüfter

2 Lüfter



0606449162769



606449162769

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.