

TP-Link Archer BE550 WLAN-Router 2.5 Gigabit Ethernet Tri-Band (2,4 GHz/5 GHz/6 GHz) Schwarz

Marke : TP-Link

Produktfamilie: Archer

Artikel-Code: ARCHER BE550

Produktname : Archer BE550

TP-Link Archer BE550. WAN-Verbindungstyp: RJ-45. WLAN-Band: Tri-Band (2,4 GHz/5 GHz/6 GHz), Top WLAN-Standard: Wi-Fi 7 (802.11be), WLAN Datentransferrate (max.): 9300 Mbit/s. Schnittstellentyp Ethernet-LAN: 2.5 Gigabit Ethernet, Ethernet LAN Datentransferraten: 10,100,1000,2500 Mbit/s. Produkttyp: Tabletop-Router, Produktfarbe: Schwarz, LED-Anzeigen: LAN, WAN. Konformitätsbescheinigungen: CE, Eidgenössische Kommunikationskommission (FCC), RoHS





WAN connection		Ports & interfaces	
Ethernet WAN *	1	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports guantity	1
DSL WAN *	×	DC-in jack	1
SIM card slot *	×	2	
3G/4G USB modem compatibility *	×	Management features	
WAN connection type	RJ-45	Reset button	1
Wireless LAN features		MU-MIMO technology	1
Wi-Fi band *	Tri-band (2.4 GHz / 5 GHz / 6 GHz)	МІМО	1
Top Wi-Fi standard *	Wi-Fi 7 (802.11be)	Security	
WLAN data transfer rate (max) *	9300 Mbit/s	Parental control	✓
Wi-Fi standards (8	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi	Protocols	
	6 (802.11ax), Wi-Fi 6E (802.11ax), Wi-Fi 7 (802.11be)	DHCP client	1
WLAN data transfer rate (first band)	574 Mbit/s	Universal Plug and Play (UPnP)	1
WLAN data transfer rate (second band)	2880 Mbit/s	Design	
WLAN data transfer rate (third	5760 Mbit/s	Product colour	Black
band)		LED indicators	LAN, WAN
Network		Product type *	Tabletop router
Ethernet LAN *	1	Certificates	
Ethernet LAN interface type * Ethernet LAN data rates	2.5 Gigabit Ethernet 10,100,1000,2500 Mbit/s	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Port forwarding	✓	Packaging content	
Port triggering	1	Cables included	LAN (RJ-45)
Automatic channel selection		AC adapter included	1
Dynamic DNS (DDNS)	·	Quick installation guide	1
Number of guest networks (2.4		Sustainability	
GHz)	1		

Network		Antenna	
Number of guest networks (5 GHz)	1	Antenna design *	Internal
Number of guest networks (6 GHz)	1	Power	
Built-in FTP server	×	Power source type *	DC
Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports * USB port *	5 ✓	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 90%
		Weight & dimensions	
		Width	76 mm

Depth

Height

231.7 mm

203 mm









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.