



## TP-Link EAP650-Outdoor 1000 Mbit/s Weiß Power over Ethernet (PoE)

**Marke :** TP-Link

**Artikel-Code:** EAP650-OUTDOOR

**Produktname :** EAP650-Outdoor

TP-Link EAP650-Outdoor. Maximale Datenübertragungsrate: 1000 Mbit/s, Ethernet LAN Datentransferraten: 10,100,1000 Mbit/s, Netzstandard: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x,.... Unterstützte Sicherheitsalgorithmen: WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise, Funktionen Service Set Identifier (SSID): Multiple SSIDs, SSID-Übertragung ein/aus. Platzierung: Stange, Wand, Produktfarbe: Weiß, Internationale Schutzart (IP-Code): IP67. Antennentyp: Intern, Antennenrichtungsart: Mit kugelförmiger Richtcharakteristik. Breite: 280,4 mm, Tiefe: 106,5 mm, Höhe: 56,8 mm



Merkmale		Anschlüsse und Schnittstellen	
2,4 GHz *	✓	Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1
5 GHz *	✓	<b>Leistung</b>	
6 GHz *	✗	Power over Ethernet (PoE) *	✓
Maximale Datenübertragungsrate *	1000 Mbit/s	<b>Design</b>	
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s	Platzierung *	Stange, Wand
Netzstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3at	Produktfarbe *	Weiß
Verkabelungstechnologie	10/100/1000Base-T(X)	Internationale Schutzart (IP-Code)	IP67
Zahl der Benutzer	250 Benutzer	Reset-Knopf	✓
MIMO	✓	Zertifizierung	CE, FCC, RoHS
MIMO-Typ	Multi User MIMO	<b>Antenne</b>	
AP-Modus-Eigenschaften anpassen	Vernetzung von Netzen	Antennentyp *	Intern
VLAN-Unterstützung	✓	Antennenrichtungsart	Mit kugelförmiger Richtcharakteristik
Quality of Service (QoS) Support	✓	<b>Gewicht und Abmessungen</b>	
<b>Sicherheit</b>		Breite	280,4 mm
Unterstützte Sicherheitsalgorithmen *	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise	Tiefe	106,5 mm
MAC Adressen Filtern	✓	Höhe	56,8 mm
Funktionen Service Set Identifier (SSID)	Multiple SSIDs, SSID-Übertragung ein/aus	<b>Betriebsbedingungen</b>	
		Relative Luftfeuchtigkeit in Betrieb	10 - 90%
		Betriebstemperatur	-30 - 70 °C
		Temperaturbereich bei Lagerung	-40 - 70 °C
		Luftfeuchtigkeit bei Lagerung	5 - 90%



4897098682098



4897098683552

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.